

# RECOMMENDED TOOLS AND CHECKERS

	Page
RECOMMENDED TOOLS AND CHECKERS .....	2





-  : An impact wrench can be used with tools with this mark. As tools without this mark are meant to be operated manually, an impact wrench cannot be used.
-  : *Une clé à chocs peut être utilisée avec les outils marqués de ce repère. Vu que les outils n'ayant pas ce repère sont conçus en vue d'une utilisation manuelle, une clé à chocs ne peut pas être utilisée.*
-  : Bei Werkzeugen mit dieser Markierung kann ein Schlagschrauber verwendet werden. Da Werkzeuge ohne diese Markierung handbetätigt werden sollten, kann kein Schlagschrauber verwendet werden.
-  : *Puede utilizarse una llave de impacto con las herramientas que presenten esta marca. Como las herramientas sin esta marca deben ser manipuladas manualmente, no se podrán utilizar con una llave de impacto.*












Illustration	Part No.	Part Name	Note
-	<b>09002-1C102 NEW</b>	Service Tool Full Set	*1 indicates tools which are included in the service tool full set (09002-1C102).
-	<b>09003-1C102 NEW</b>	Service Tool Half Set	*2 indicates tools which are included in the service tool half set (09003-1C102).
	<b>09003-2C100 NEW</b>	Insulated Tool Set	This set consists of the following 5 parts.
	<b>(09012-4C100)</b>	( Insulated Deep Socket 8mm )	Size (Hexagon): 8 mm Square drive 9.5 mm
	<b>(09012-4C110)</b>	( Insulated Deep Socket 10mm )	Size (Hexagon): 10 mm Square drive 9.5 mm
	<b>(09021-1C200)</b>	( Insulated Ratchet Handle )	Square drive 9.5 mm
	<b>(09072-2C100)</b>	( Insulated Torque Wrench 5 to 25 N*m )	Torque range: 5 to 25 N*m Square drive 9.5 mm
	<b>(09005-1C200)</b>	( Insulated Tool Case )	In order to prevent the insulation coating on the tools from deterioration caused by direct sunlight, be sure to store the insulated tools in this case.
	<b>09005-1C100</b>	Service Tool Case	*2
	<b>09010-3C100</b>	Hexagon Wrench Set	
	<b>(09005-1C110)</b>	(Hard Case)	
	<b>(09013-6C100)</b>	( Hexagon Socket Wrench 5 )	Use hexagon bit 09013-6C900 for bit replacement. Square drive 9.5 mm
	<b>(09013-6C110)</b>	( Hexagon Socket Wrench 6 )	Use hexagon bit 09013-6C910 for bit replacement. Square drive 9.5 mm
	<b>(09013-6C120)</b>	( Hexagon Socket Wrench 8 )	Use hexagon bit 09013-6C920 for bit replacement. Square drive 9.5 mm
	<b>(09013-6C130)</b>	( Hexagon Socket Wrench 10 )	Use hexagon bit 09013-6C930 for bit replacement. Square drive 9.5 mm
	<b>(09013-6C140)</b>	( Hexagon Socket Wrench 12 )	Use hexagon bit 09013-6C940 for bit replacement. Square drive 9.5 mm





Illustration	Part No.	Part Name	Note
	(09013-7C100)	( Straight Hexagon ) Wrench 10	
	(09013-7C110)	( Straight Hexagon ) Wrench 12	
	(09013-7C120)	( Straight Hexagon ) Wrench 14	
	(09013-7C130)	( Straight Hexagon ) Wrench 17	
	(09013-7C140)	( Straight Hexagon ) Wrench 19	
	(09013-7C150)	( Straight Hexagon ) Wrench 21	
	(09013-7C160)	( Straight Hexagon ) Wrench 24	
	<b>09010-3C110</b>	Hexagon Socket Wrench Set	
	(09005-1C120)	(Soft Case)	
	(09013-6C100)	( Hexagon Socket ) Wrench 5	
	(09013-6C110)	( Hexagon Socket ) Wrench 6	
	(09013-6C120)	( Hexagon Socket ) Wrench 8	
	(09013-6C130)	( Hexagon Socket ) Wrench 10	
(09013-6C140)	( Hexagon Socket ) Wrench 12		
	<b>09013-6C900</b>	Hexagon Bit 5	Replacement part for hexagon socket wrench 5 (09013-6C100).
	<b>09013-6C910</b>	Hexagon Bit 6	Replacement part for hexagon socket wrench 6 (09013-6C110).












Illustration	Part No.	Part Name	Note
	<b>09013-6C920</b>	Hexagon Bit 8	Replacement part for hexagon socket wrench 8 (09013-6C120).
	<b>09013-6C930</b>	Hexagon Bit 10	Replacement part for hexagon socket wrench 10 (09013-6C130).
	<b>09013-6C940</b>	Hexagon Bit 12	Replacement part for hexagon socket wrench 12 (09013-6C140).
	<b>09010-3C120</b>	"TORX" Socket Wrench Set	
	<b>(09005-1C120)</b>	Soft Case	
	<b>(09013-1C100)</b>	"TORX" Socket Wrench T20	 3.8 mm The "TORX" bit is replaceable. Square drive 9.5 mm For removing and installing "TORX" screw or bolt
	<b>(09013-1C110)</b>	"TORX" Socket Wrench T25	 4.4 mm 
	<b>(09013-1C120)</b>	"TORX" Socket Wrench T30	 5.5 mm T20 = 3.8 mm T25 = 4.4 mm T30 = 5.5 mm
	<b>(09013-1C130)</b>	"TORX" Socket Wrench T40	 6.6 mm T40 = 6.6 mm T45 = 7.8 mm T50 = 8.8 mm
	<b>(09013-1C140)</b>	"TORX" Socket Wrench T45	 7.8 mm
	<b>(09013-1C150)</b>	"TORX" Socket Wrench T50	 8.8 mm
	<b>09013-1C900</b>	"TORX" Bit T20	Replacement part for "TORX" socket wrench T20 (09013-1C100).
	<b>09013-1C910</b>	"TORX" Bit T25	Replacement part for "TORX" socket wrench T25 (09013-1C110).
	<b>09013-1C920</b>	"TORX" Bit T30	Replacement part for "TORX" socket wrench T30 (09013-1C120).
	<b>09013-1C930</b>	"TORX" Bit T40	Replacement part for "TORX" socket wrench T40 (09013-1C130).
	<b>09013-1C940</b>	"TORX" Bit T45	Replacement part for "TORX" socket wrench T45 (09013-1C140).





Illustration	Part No.	Part Name	Note
	<b>09013-1C950</b>	"TORX" Bit T50	Replacement part for "TORX" socket wrench T50 (09013-1C150).
	<b>09011-1C100</b>	Socket Wrench 8 mm 6P	Square drive 9.5 mm
	<b>09011-1C110</b>	Socket Wrench 10 mm 6P	*1, *2 Square drive 9.5 mm
	<b>09011-1C120</b>	Socket Wrench 12 mm 6P	*1, *2 Square drive 9.5 mm
	<b>09011-1C130</b>	Socket Wrench 13 mm 6P	Square drive 9.5 mm
	<b>09011-1C140</b>	Socket Wrench 14 mm 6P	Square drive 9.5 mm
	<b>09011-1C500</b>	Socket Wrench 12 mm 12P	Square drive 9.5 mm
	<b>09011-1C510</b>	Socket Wrench 14 mm 12P	*1, *2 Square drive 9.5 mm
	<b>09011-1C520</b>	Socket Wrench 17 mm 12P	*2 Square drive 9.5 mm
	<b>09011-1C530</b>	Socket Wrench 19 mm 12P	*2 Square drive 9.5 mm
	<b>09011-1C540</b>	Socket Wrench 13 mm 12P	Square drive 9.5 mm
	<b>09011-2C100</b>	Socket Wrench 14 mm 6P	Square drive 12.7 mm
	<b>09011-2C110</b>	Socket Wrench 17 mm 6P	Square drive 12.7 mm
	<b>09011-2C120</b>	Socket Wrench 19 mm 6P	Square drive 12.7 mm





Illustration	Part No.	Part Name	Note
	<b>09011-2C500</b>	Socket Wrench 17 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C510</b>	Socket Wrench 19 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C520</b>	Socket Wrench 21 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C530</b>	Socket Wrench 22 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C540</b>	Socket Wrench 23 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C550</b>	Socket Wrench 24 mm 12P	*1 Square drive 12.7 mm
	<b>09011-2C560</b>	Socket Wrench 26 mm 12P	Square drive 12.7 mm
	<b>09011-2C570</b>	Socket Wrench 27 mm 12P	Square drive 12.7 mm
	<b>09011-2C580</b>	Socket Wrench 29 mm 12P	Square drive 12.7 mm
	<b>09011-2C590</b>	Socket Wrench 30 mm 12P	Square drive 12.7 mm
	<b>09011-2C600</b>	Socket Wrench 32 mm 12P	Square drive 12.7 mm
	<b>09011-4C100</b>	Socket Wrench 46 mm 12P	Square drive 19.0 mm
	<b>09011-4C110</b>	Socket Wrench 50 mm 12P	Square drive 19.0 mm
	<b>09011-4C120</b>	Socket Wrench 39 mm 12P	Square drive 19.0 mm
 	<b>09011-3C100</b>	Impact Socket Wrench 21mm	For wheel nut Square drive 12.7 mm
	<b>09011-3C301</b>	Socket Wrench 21mm for Aluminum Wheel	Square drive 12.7 mm











Illustration	Part No.	Part Name	Note
	<b>09011-3C200</b>	Spark Plug Wrench 20.8 mm	*1, *2 Square drive 9.5 mm
	<b>09011-3C210</b>	Spark Plug Wrench 16 mm	*1, *2 Square drive 9.5 mm
	<b>09011-3C220</b>	Spark Plug Wrench 14 mm	Square drive 9.5 mm
	<b>09011-3C400</b>	Phillips Socket Wrench	Use phillips bit 09011-3C900 for bit replacement. Square drive 9.5 mm
	<b>09011-3C500</b>	Combination Socket Wrench 41 x 20 mm	Size (Hexagon): 41 mm Size (Square): 20 mm Square drive 19 mm
	<b>09011-3C510</b>	Inner Nut adaptor 20 mm 8P	Size (Hexagon): 41 mm Size (Square): 20 mm
	<b>09011-3C900</b>	Phillips Bit	Replacement part for phillips socket wrench (09011-3C400).
	<b>09011-5C100</b>	Universal Socket Wrench 8 mm 6P	Square drive 9.5 mm
	<b>09011-5C110</b>	Universal Socket Wrench 10 mm 6P	Square drive 9.5 mm
	<b>09011-5C120</b>	Universal Socket Wrench 12 mm 6P	Square drive 9.5 mm
	<b>09012-1C100</b>	Deep Socket Wrench 8 mm 6P	Square drive 9.5 mm
	<b>09012-1C110</b>	Deep Socket Wrench 10 mm 6P	Square drive 9.5 mm
	<b>09012-1C120</b>	Deep Socket Wrench 12 mm 6P	Square drive 9.5 mm
	<b>09012-1C130</b>	Deep Socket Wrench 14 mm 6P	Square drive 9.5 mm











Illustration	Part No.	Part Name	Note
	<b>09012-2C500</b>	Deep Socket Wrench 17 mm 12P	Square drive 12.7 mm
	<b>09012-2C510</b>	Deep Socket Wrench 19 mm 12P	Square drive 12.7 mm
	<b>09012-2C520</b>	Deep Socket Wrench 24 mm 12P	Square drive 12.7 mm
	<b>09012-2C530</b>	Deep Socket Wrench 27 mm 12P	Square drive 12.7 mm
	<b>09012-2C540</b>	Deep Socket Wrench 30 mm 12P	Square drive 12.7 mm
	<b>09012-3C100</b>	Bolt/Nut Grip Deep Socket 8 mm	Size : 8 mm Style: 6 point Length: 55 mm Square drive 9.5 mm
	<b>09012-3C110</b>	Bolt/Nut Grip Deep Socket 10 mm	Size: 10 mm Style: 6 point Length: 55 mm Square drive 9.5 mm
	<b>09013-1C160 NEW</b>	"TORX Plus" Socket Wrench	 6.6 mm Square drive 9.5 mm 40 IP = 6.6 mm
	<b>09013-1C200</b>	Short "TORX" Socket Wrench T30	 5.5 mm The "TORX" bit is replaceable. Square drive 9.5 mm For removing and installing "TORX" screw or bolt
	<b>09013-1C300</b>	Long "TORX" Socket Wrench T30	 5.5 mm T30 = 5.5 mm
	<b>09013-1C310</b>	Long "TORX" Socket Wrench T40	 6.6 mm T40 = 6.6 mm
	<b>09013-1C960</b>	Long "TORX" Bit T30	Replacement part for long "TORX" socket wrench T30 (09013-1C300).
	<b>09013-1C970</b>	Long "TORX" Bit T40	Replacement part for long "TORX" socket wrench T40 (09013-1C310).
	<b>09013-1C980</b>	Short "TORX" Bit T30	Replacement part for short "TORX" socket wrench T30 (09013-1C200).













Illustration	Part No.	Part Name	Note
	<b>09013-1C500</b>	"TORX" Socket Wrench E5	E5 = 4.7 mm Square drive 9.5 mm
	<b>09013-1C510</b>	"TORX" Socket Wrench E6	E6 = 5.6 mm Square drive 9.5 mm
	<b>09013-1C520</b>	"TORX" Socket Wrench E7	E7 = 6.1 mm Square drive 9.5 mm
	<b>09013-1C530</b>	"TORX" Socket Wrench E8	E8 = 7.4 mm Square drive 9.5 mm
	<b>09013-1C540</b>	"TORX" Socket Wrench E10	E10 = 9.4 mm Square drive 9.5 mm
	<b>09013-1C551 NEW</b>	"TORX" Socket Wrench E14	E14 = 12.8 mm Square drive 12.7 mm
	<b>09013-1C560 NEW</b>	"TORX" Socket Wrench E16	E16 = 14.66 mm Square drive 12.7 mm
	<b>09013-1C580</b>	"TORX" Socket Wrench E20	E20 = 18.4 mm Square drive 12.7 mm
	<b>09013-2C100</b>	"TORX" Socket Wrench T30H for Tamper Resistant Fasteners  5.5 mm	The "TORX" bit is replaceable. Square drive 9.5 mm For removing and installing "TORX" screw or bolt 
	<b>09013-2C110</b>	"TORX" Socket Wrench T50H for Tamper Resistant Fasteners  8.8 mm	
	<b>09013-2C120</b>	"TORX" Socket Wrench T55H for Tamper Resistant Fasteners  9.9 mm	
	<b>09013-2C900</b>	"TORX" Bit T30H for Tamper Resistant Fasteners	Replacement part for "TORX" socket wrench T30H for tamper resistant fasteners (09013-2C100).
	<b>09013-2C910</b>	"TORX" Bit T50H for Tamper Resistant Fasteners	Replacement part for "TORX" socket wrench T50H for tamper resistant fasteners (09013-2C110).
	<b>09013-2C920</b>	"TORX" Bit T55H for Tamper Resistant Fasteners	Replacement part for "TORX" socket wrench T55H for tamper resistant fasteners (09013-2C120).
	<b>09013-6C090</b>	Hexagon Socket Wrench 4	Use hexagon bit 4 09013-6C890 for bit replacement. Square drive 9.5 mm







Illustration	Part No.	Part Name	Note
	<b>09013-6C500</b>	Long Hexagon Socket Wrench 5	Use long hexagon bit 5 09013-6C950 for bit replacement. Square drive 9.5 mm
	<b>09013-6C510</b>	Long Hexagon Socket Wrench 6	Use long hexagon bit 6 09013-6C960 for bit replacement. Square drive 9.5 mm
	<b>09013-6C520</b>	Long Hexagon Socket Wrench 8	Use long hexagon bit 8 09013-6C970 for bit replacement. Square drive 9.5 mm
	<b>09013-6C890</b>	Hexagon Bit 4	Replacement part for hexagon socket wrench 4 (09013-6C090).
	<b>09013-6C950</b>	Long Hexagon Bit 5	Replacement part for long hexagon socket wrench 5 (09013-6C500).
	<b>09013-6C960</b>	Long Hexagon Bit 6	Replacement part for long hexagon socket wrench 6 (09013-6C510).
	<b>09013-6C970</b>	Long Hexagon Bit 8	Replacement part for long hexagon socket wrench 8 (09013-6C520).
	<b>09013-7C300</b>	Double Hexagon Wrench 8 mm	Square drive 12.7 mm
	<b>09013-7C310</b>	Double Hexagon Wrench 10 mm	Square drive 12.7 mm
	<b>09013-7C400</b>	L Shape Hex-Key Wrench Set	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm
	<b>09017-1C100</b>	Union Nut Wrench 10 mm	Square drive 9.5 mm
	<b>09017-1C110</b>	Union Nut Wrench 12 mm	Square drive 9.5 mm
	<b>09017-1C120</b>	Union Nut Wrench 14 mm	Square drive 9.5 mm
	<b>09017-1C130</b>	Union Nut Wrench 17 mm	Square drive 12.7 mm
	<b>09017-1C140</b>	Union Nut Wrench 19 mm	Square drive 12.7 mm







Illustration	Part No.	Part Name	Note
	<b>09017-1C200</b>	Ball Joint Lock Nut Wrench 17 mm	
	<b>09017-1C210</b>	Ball Joint Lock Nut Wrench 19 mm	
	<b>09017-1C220</b>	Ball Joint Lock Nut Wrench 22 mm	
	<b>09021-1C100</b>	Ratchet Handle	*1, *2 Square drive 9.5 mm Size 180 mm
	<b>09021-1C110</b>	Ratchet Handle	Square drive 12.7 mm Size 250 mm
	<b>09021-2C100</b>	Spinner Handle	Square drive 9.5 mm
	<b>09021-2C110</b>	Spinner Handle	*1 Square drive 12.7 mm
	<b>09021-3C100</b>	Sliding T-tipe Handle	*1, *2 Square drive 9.5 mm Size 200 mm
	<b>09021-3C110</b>	Sliding T-tipe Handle	Square drive 12.7 mm Size 250 mm
	<b>09021-3C200</b>	L-type Handle	Square drive 19.0 mm
	<b>09022-1C100</b>	Extension Bar 75 mm	*1, *2 Square drive 9.5 mm
	<b>09022-1C110</b>	Extension Bar 100 mm	Square drive 9.5 mm
	<b>09022-1C120</b>	Extension Bar 150 mm	*1, *2 Square drive 9.5 mm
	<b>09022-1C130</b>	Extension Bar 270 mm	*1 Square drive 9.5 mm
	<b>09022-1C300</b>	Extension Bar 75 mm	Square drive 12.7 mm









Illustration	Part No.	Part Name	Note
	<b>09022-1C310</b>	Extension Bar 150 mm	*1 Square drive 12.7 mm
	<b>09022-1C320</b>	Extension Bar 270 mm	Square drive 12.7 mm
	<b>09022-1C330</b>	Extension Bar 990 mm	Square drive 12.7 mm
	<b>09022-1C700</b>	Extension Bar 250 mm	Length : 250 mm Square drive 19 mm
	<b>09022-1C500</b>	Tilt Extension Bar 30 mm	Square drive 9.5 mm
	<b>09022-1C510</b>	Tilt Extension Bar 75 mm	Square drive 9.5 mm
	<b>09022-1C520</b>	Tilt Extension Bar 150 mm	Square drive 9.5 mm
	<b>09022-3C100</b>	Socket Adaptor	*1 Square drive 12.7 mm to 9.5 mm
	<b>09022-3C110</b>	Socket Adaptor	*1 Square drive 9.5 mm to 12.7 mm
	<b>09022-3C200</b>	Universal Joint	*1, *2 Square drive 9.5 mm
	<b>09022-3C210</b>	Universal Joint	Square drive 12.7 mm
	<b>09025-00010</b>	Small Torque Wrench	
	<b>09030-2C100</b>	Combination Wrench Set	
	<b>(09032-2C110)</b>	( Combination Wrench 10 mm )	
	<b>(09032-2C120)</b>	( Combination Wrench 12 mm )	
	<b>(09032-2C130)</b>	( Combination Wrench 14 mm )	





Illustration	Part No.	Part Name	Note
	<b>(09032-2C140)</b>	( Combination Wrench 17 mm )	
	<b>09032-2C100</b>	Long Combination Wrench 14 mm	
	<b>09031-1C100</b>	Long Offset Wrench 8 x 10 mm	
	<b>09031-1C110</b>	Long Offset Wrench 10 x 12 mm	*1, *2
	<b>09031-1C190</b>	Long Offset Wrench 11 x 13 mm	
	<b>09031-1C120</b>	Long Offset Wrench 12 x 14 mm	*1
	<b>09031-1C130</b>	Long Offset Wrench 14 x 17 mm	*1, *2
	<b>09031-1C140</b>	Long Offset Wrench 17 x 19 mm	
	<b>09031-1C150</b>	Long Offset Wrench 19 x 21 mm	*1, *2
	<b>09031-1C160</b>	Long Offset Wrench 21 x 23 mm	
	<b>09031-1C170</b>	Long Offset Wrench 22 x 24 mm	*1, *2
	<b>09031-1C180</b>	Long Offset Wrench 24 x 27 mm	
	<b>09031-1C500</b>	Short Offset Wrench 8 x 10 mm	*1
	<b>09031-1C510</b>	Short Offset Wrench 10 x 12 mm	
	<b>09031-1C520</b>	Short Offset Wrench 11 x 13 mm	
	<b>09031-1C530</b>	Short Offset Wrench 12 x 14 mm	*1






Illustration	Part No.	Part Name	Note
	<b>09032-1C100</b>	Open End Wrench 6 x 7 mm	
	<b>09032-1C110</b>	Open End Wrench 8 x 9 mm	
	<b>09032-1C120</b>	Open End Wrench 8 x 10 mm	*1, *2
	<b>09032-1C130</b>	Open End Wrench 10 x 12 mm	*1, *2
	<b>09032-1C140</b>	Open End Wrench 12 x 14 mm	*1, *2
	<b>09032-1C150</b>	Open End Wrench 14 x 17 mm	*1, *2
	<b>09032-1C160</b>	Open End Wrench 17 x 19 mm	*1, *2
	<b>09032-1C170</b>	Open End Wrench 21 x 23 mm	
	<b>09032-1C180</b>	Open End Wrench 22 x 24 mm	
	<b>09032-1C190</b>	Angled Open End Wrench 12 x 14 mm	
	<b>09033-1C100</b>	Hub Nut Wrench 21mm	*1, *2
	<b>09041-1C100</b>	Phillips Stubby Screwdriver 25mm	*1, *2
	<b>09041-1C110</b>	Phillips Screwdriver 75 mm	*1
	<b>09041-1C120</b>	Phillips Screwdriver 100 mm	*1, *2
	<b>09041-1C130</b>	Phillips Screwdriver 150 mm	*1
	<b>09041-1C140</b>	Phillips Screwdriver 250 mm	









Illustration	Part No.	Part Name	Note	
	<b>09041-1C500</b>	Flat head Stubby Screwdrive 25mm	*1, *2	
	<b>09041-1C510</b>	Flat head Screwdrive 75 mm	*1	
	<b>09041-1C520</b>	Flat head Screwdrive 100 mm	*1, *2	
	<b>09041-1C530</b>	Flat head Screwdrive 150 mm	*1	
	<b>09041-1C540</b>	Flat head Screwdrive 250 mm		
	<b>09041-1C550</b>	Thin Flat head Screwdrive	*1, *2	
	<b>09041-1C150</b>	Short Phillips Screwdrive 15 mm		
	<b>09041-1C560</b>	Phillips Micro Screwdrive		
	<b>09041-2C100</b>	Socket drive 5.5 mm		
	<b>09041-2C110</b>	Socket drive 7 mm		
	<b>09041-2C120</b>	Socket drive 8 mm	*1	
	<b>09041-2C130</b>	Socket drive 10 mm	*1	
	<b>09041-2C200</b>	"TORX" Screwdrive T10H for Tamper Resistant Fasteners	 <p>For removing and installing "TORX" screw or bolt</p> <p>T10 = 2.7 mm (0.106 in.)  T20 = 3.8 mm (0.150 in.)  T25 = 4.4 mm (0.173 in.)  T30 = 5.5 mm (0.217 in.)</p>	
	<b>09041-2C210</b>	"TORX" Screwdrive T20H for Tamper Resistant Fasteners		2.7 mm
	<b>09041-2C220</b>	"TORX" Screwdrive T25H for Tamper Resistant Fasteners		3.8 mm
	<b>09041-2C230</b>	"TORX" Screwdrive T30H for Tamper Resistant Fasteners		4.4 mm
			5.5 mm	
















Illustration	Part No.	Part Name	Note
	<b>09042-1C102 NEW</b>	Wrench,Monkey 250mm	*1, *2
	<b>09042-1C200</b>	Pliers	Size 150 mm
	<b>09042-1C210</b>	Pliers	*1, *2 Size 200 mm
	<b>09042-1C300</b>	Needle Nose Plier	*1, *2 Size 160 mm
	<b>09042-1C400</b>	Nipper	
	<b>09042-1C500</b>	Water Pump Pliers	
	<b>09042-1C600</b>	Hog Ring Pliers	
	<b>09043-38100</b>	Hexagon 10 mm Wrench	
	<b>09050-00032</b>	Air Drill	
	<b>(09050-00210)</b>	(Chuck Set)	
	<b>(09050-00220)</b>	(Handle)	
	<b>09050-00071</b>	Air Duster	
	<b>(09050-00600)</b>	(Nozzle)	
	<b>09050-10010</b>	Air Powered Ratchet	
	<b>(09050-00060)</b>	(Air Tool Oil)	
	<b>(09050-01010)</b>	( Wrench Shank Sub-assembly )	



















Illustration	Part No.	Part Name	Note
	(09050-01020)	( Ratchet Shank Repair Kit )	
	(09050-01030)	( Head Housing Assembly )	
	(09050-01040)	(Gear Repair Kit)	
	(09050-01050)	(Motor Assembly)	
	(09050-01060)	( Throttle Valve Repair Kit )	
	(09050-01070)	( Throttle Lever Repair Kit )	
	(09050-01080)	(Silencer Ring)	
	(09050-01090)	(Inlet Union)	
	(09050-01100)	( Air Powered Ratchet Crank )	
	<b>09050-20010</b>	Air Riveter	
	(09050-02010)	(Dust Cap)	
	(09050-02020)	(Nose Piece No.1)	
	(09050-02030)	(Nose Piece No.2)	
	(09050-02040)	(Nose Piece No.3)	
	<b>09050-02050</b>	Nose Piece No.4	Optional tool for Recommended Tool No. 09050-20010
	<b>09051-1C100</b>	Hammer	*1, *2












Illustration	Part No.	Part Name	Note
	<b>09051-1C110</b>	Plastic Hammer	
	<b>09051-1C200</b>	Brass Bar	*1 Size 220 mm, $\phi$ 16
	<b>09051-1C300</b>	Chisel	Blade width 19 mm
	<b>09051-1C400</b>	Pin Punch	Pin diameter 3 mm
	<b>09051-1C410</b>	Pin Punch	Pin diameter 5 mm
	<b>09051-1C500</b>	Center Punch	
	<b>09052-1C100</b>	Gasket Scraper Set	
	<b>(09052-1C110)</b>	(Gasket Scraper)	*1
	<b>(09052-1C120)</b>	( Gasket Scraper ) U-Type	
	<b>(09052-1C130)</b>	( Gasket Scraper ) P-Type	
	<b>(09052-1C140)</b>	(Oil Stone)	Length 75mm
	<b>(09052-1C150)</b>	(Case)	
	<b>09052-1C200</b>	Valve Cap Wrench	
	<b>09052-1C300</b>	Oil Stone	Length 120 mm
	<b>09053-1C100</b>	Magnet Hand	*1
	<b>09053-1C200</b>	Hose Plug Set	













Illustration	Part No.	Part Name	Note
	<b>(09053-1C210)</b>	(Hose Plug No.1)	*1
	<b>(09053-1C220)</b>	(Hose Plug No.2)	
	<b>09060-60350</b>	Revet Cutter	
	<b>09061-1C100</b>	Clip Remover	Length 172 mm Tip opening width 6 mm
	<b>09061-1C110</b>	Clip Remover	Length 192.5 mm Tip opening width 10 mm
	<b>09061-1C300</b>	Moulding Remover Set	
	<b>(09061-1C310)</b>	(Moulding Remover A)	
	<b>(09061-1C320)</b>	(Moulding Remover B)	
	<b>(09061-1C330)</b>	(Moulding Remover C)	
	<b>(09061-1C340)</b>	(Moulding Remover D)	
	<b>09062-1C101 NEW</b>	Vise Plier 50mm	
	<b>09062-1C200</b>	File Set	
	<b>09071-1C100</b>	Spark Plug Gap Gauge	*1 Size 0.8, 0.9, 1.0, 1.1 mm
	<b>09071-1C200</b>	Thickness Gauge 14PCS	Range 0.03 - 0.5 mm
	<b>09071-1C210</b>	Thickness Gauge 18PCS	*1 Range 0.08 - 0.5 mm















Illustration	Part No.	Part Name	Note
	<b>09072-1C100</b>	Tape Measure 2 m	
	<b>09072-1C110</b>	Tape Measure 3.5 m	
	<b>09072-1C200</b>	Vernier Calipers 150 mm	
	<b>09072-1C210</b>	Vernier Calipers 300 mm	
	<b>09080-1C110 NEW</b>	Toyota Electrical Tester Set	An instruction manual and the following 2 parts are included
	<b>(09082-1C100)</b>	(Test Lead)	1 red and 1 black lead Harness length: 800 mm (31.50 in.) Diameter: 2.0 mm (0.0787 in.)
	<b>(09082-3C110)</b>	(Tester Case)	
	<b>09080-2C100 NEW</b>	Test Lead Set	The following 4 parts are included
	<b>(09082-1C110)</b>	(Base Lead)	1 red and 1 black lead Harness length: 1500 mm (59.06 in.)
	<b>(09082-1C120)</b>	(Test Bar)	1 red and 1 black bar
	<b>(09082-1C130)</b>	(Pin2.0)	1 red and 1 black pin Diameter: 2.0 mm (0.0787 in.)
	<b>(09082-1C140)</b>	(Pin0.5)	1 red and 1 black pin Diameter: 0.5 mm (0.0197 in.)
	<b>09080-2C110 NEW</b>	AC/DC400A Probe	An instruction manual and the following part is included
	<b>(09082-3C120)</b>	(Probe Case)	
	<b>09082-1C150 NEW</b>	Alligator Clip	1 red and 1 black clip
	<b>09082-1C160 NEW</b>	IC Clip	1 red and 1 black clip

















Illustration	Part No.	Part Name	Note
	<b>09082-2C100 NEW</b>	Fast Acting Fuse2A	
	<b>09082-2C110 NEW</b>	Fast Acting Fuse15A	
	<b>09090-04020</b>	Engine Sling Device	
	<b>(09091-00100)</b>	(Hook A)	
	<b>(09091-00200)</b>	(Hook B)	
	<b>09090-06000</b>	Transmission Repair Stand	For setting the transmission in a vise (W & N series transmission only)
	<b>09091-1C100</b>	Oil Pan Seal Cutter	
	<b>09200-00011</b>	Engine Adjust Kit	
	<b>(09203-00010)</b>	(Thickness Gauge)	
	<b>(09855-10011)</b>	(Wrench 7 x 8 mm)	
	<b>(09856-10010)</b>	(Oil Stone)	
	<b>(09857-00031)</b>	( Spark Plug Gap Gauge )	
	<b>09216-00010</b>	V Belt Remover	
	<b>09216-00021</b>	Belt Tension Gauge	
	<b>09216-00030</b>	Belt Tension Gauge Cable	
	<b>09216-10050</b>	Master Gauge	






















Illustration	Part No.	Part Name	Note
	<b>09230-40010</b>	Radiator Cap Tester	Max Pressure : 200kPa (2.03 kg/cm <sup>2</sup> , 29 psi)
	<b>09230-40020</b>	Radiator Cap Tester	Max Pressure : 300kPa (3.05 kg/cm <sup>2</sup> , 43 psi)
	<b>09231-40010</b>	Radiator Cap Tester Adapter Set A	
	<b>(09231-04010)</b>	Adapter A	
	<b>(09231-04020)</b>	Adapter A with hose	
	<b>09231-40020</b>	Radiator Cap Tester Adapter Set B	
	<b>(09231-04030)</b>	Adapter B	
	<b>(09231-04040)</b>	Adapter B with hose	
	<b>09231-40030</b>	Radiator Cap Tester Adapter Set C	
	<b>09860-11013</b>	Caburetor drive Set	
	<b>09904-00010</b>	Expander Set	For removing and installing snap ring
	<b>(09904-00020)</b>	(No.1 Claw)	Set of 2
	<b>(09904-00030)</b>	(No.2 Claw)	Set of 2
	<b>(09904-00040)</b>	(No.3 Claw)	Set of 2
	<b>(09904-00050)</b>	(No.4 Claw)	Set of 2
	<b>(09904-00060)</b>	(No.5 Claw)	Set of 2

Illustration	Part No.	Part Name	Note
	(09904-00070)	(No.6 Claw)	Set of 2
	(09904-00080)	(No.7 Claw)	Set of 2
	09905-00012	Snap Ring No.1 Expander	For removing and installing snap ring
	09905-00013	Snap Ring Pliers	
	(09904-00090)	(Claw Set)	Set of 2
	09924-12361	Deep Socket Wrench 36 mm 12P	Square drive 12.7 mm
	09924-12411	Deep Socket Wrench 41 mm 12P	Square drive 12.7 mm

