Distribution Center: Vehicle Storage

Parking slot lines are drawn on the paved storage area to make sufficient space between vehicles.

Sweeper machine is used to remove gravel on storage yard.

Vehicles are parked in a warehouse to prevent vehicles from getting damaged (falling tree leaves, bird droppings, etc.).

Transport

Trailer driver wears a pair of gloves during operation.

Soft rubber protectors are put on trailer pillars to prevent vehicle doors from getting damaged.

Plastic cover is provided for front of vehicle to prevent stone chips during driving transport.

Dealer: Vehicle Storage

Parking slot lines are drawn on the paved storage area to make sufficient space between vehicles.

Vehicles are stored under roof to prevent vehicles from getting damaged (falling tree leaves, bird droppings, etc.).

Parking location numbers are provided on the parking slots.

Negative battery terminal is disconnected to prevent the battery from discharging.

Tire stoppers are provided to prevent front bumper from touching the pole.

To prevent tire flat spot damage, the tire pressure is periodically measured and maintained in the sufficient condition.

Dealer: Workshop

Washer nozzle protector is provided to prevent vehicle body from scratching.

Rubber protector is provided to the car lift to prevent vehicle door dent.

Worker wears a buckleless belt to prevent vehicle body from scratching.

Pre-Delivery Service is performed thoroughly.

Protective covers are used to prevent the seat, floor, steering wheel and shift knob from getting dirty. (It is a good idea to cover the scuff plate with the floor cover.)

Workshop floor is cleaned.